

Portable Noise Measurement Report

South Meadow Drive, Glen Burnie, MD 21060

Maryland Aviation Administration

July 2026



Introduction

PURPOSE

The purpose of the *Portable Noise Measurement Report* is to summarize aircraft and community noise levels at a specific location upon request of a homeowner. The program is offered by the Maryland Department of Transportation Maryland Aviation Administration (MAA), with technical support and report preparation provided by Harris Miller Miller & Hanson Inc. (HMMH) and Airport Design Consultants, Inc. (ADCI).

NOISE DATA

It should be noted that the noise data provided in this report represents noise and operating levels only during the period of the measurements. Noise levels associated with aircraft overflights can vary with the number of operations, wind and weather patterns, temperatures, pilot procedures and Air Traffic Control instruction, and other variables.

MONITORING TIME AND LOCATION

This report presents the measured aircraft and community noise levels from June 13, 2026 to June 28, 2026, at S Meadow Drive, Glen Burnie, MD 21060. The monitoring location is approximately 3.9 statute miles from the center of Baltimore/Washington International Thurgood Marshall (BWI Marshall) Airport. **Figure 1** shows the location of the measurement site (marked as BW363) relative to BWI Marshall.




Figure 1. Noise Monitoring Location in Relation to BWI Marshall

Site BW363 Summary

? WHEN WAS NOISE MEASURED

Saturday, June 13, 2026 to
Sunday, June 28, 2026

16
DAYS

JUNE / JULY 2026	S	M	T	W	T	F	S
	7	8	9	10	11	12	13
	14	15	16	17	18	19	20
	measurements						
	21	22	23	24	25	26	27
	measurements						
	28	29	30	1	2	3	4

✈ HOW MANY AIRCRAFT NOISE EVENTS OCCURRED AND WHAT WERE THEY



TOP 3 MOST FREQUENT AIRCRAFT DURING THE MEASUREMENT PERIOD

Rank	Aircraft type	Operation type and Runway
1	Boeing 737-800 MAX 	Arrival, 28
2	Boeing 737-700 	Arrival, 28
3	Boeing 737-800 	Arrival, 28

🔍 CONCLUSION

During the 16-day measurement period, the Day Night Average Noise Level (DNL) from aircraft noise events was 49 decibels (dB), while the DNL from community noise was 52 dB.

FAA's threshold for land use compatibility is an aircraft-only DNL of 65 dB based on annual average daily aircraft operations.

Aircraft DNL	Community DNL	Total DNL	FAA Threshold
49 dB	52 dB	54 dB	65 dB

Aircraft Operations

FLIGHTS DURING MEASUREMENT PERIOD

Operations at BWI Marshall fluctuate on a daily basis. During the measurement period, there were 10,681 flights in and out of BWI Marshall (5,335 arrivals, 5,346 departures), in addition to overflights to other airports.

FIXED-WING OPERATIONS

The number of flights per day ranged from 609 to 758. Flights in the vicinity of this site are primarily arrivals to BWI Marshall Runway 28 and departures from Runway 10. BWI Marshall has three runways, designated as Runway 10/28, Runway 15R/33L, and Runway 15L/33R. Runway 10/28 is 10,502 feet in length, while Runway 15R/33L is 9,500 feet in length. Runway 15L/33R is 5,000 feet in length and is only used by certain aircraft. As aircraft cannot arrive and depart from the same runway, BWI Marshall generally operates in two configurations: west flow (primarily departures from Runway 28 and arrivals to Runway 33L) and east flow (primarily departures from Runway 15R and arrivals to Runway 10). On an annual basis, west flow is used approximately 70% of the time, while east flow is used approximately 30% of the time. During west flow, aircraft operations primarily consist of arrivals to BWI Marshall Runway 33L and departures from Runway 28. During east flow, aircraft operations primarily consist of departures from BWI Marshall Runway 15R and arrivals to Runway 10. Arrivals to BWI Marshall were generally 900 to 1,100 feet above ground level at their point of closest approach to the measurement site. Departures from BWI Marshall were generally 1,700 to 2,800 feet above ground level at their point of closest approach to the measurement site. During the measurement period, the west flow runway use was 72% (**Figure 2**), and the east flow runway use was 28% (**Figure 3**).





Figure 2. West Flow Runway Use During Measurement Period




Figure 3. East Flow Runway Use During Measurement Period

Methodology and Location

MEASUREMENT LOCATION AND SETUP

Aircraft noise levels were measured from June 13, 2026 to June 28, 2026 , at S Meadow Dr., Glen Burnie, MD 21060.

The noise monitor is a Type I sound level meter and was regularly calibrated. Additionally, the system was checked every two to four days during the measurements to ensure proper operation. During setup, a baseline threshold was established for the noise monitor. Once the sound level exceeded the baseline threshold for 5 seconds, a noise event was recorded. For each noise event, the sound level meter recorded date, time, duration, and noise levels.

The noise monitor was placed in the backyard of the residence. Notable noise sources at this site included aircraft overflights to and from BWI Marshall as well as overflights to and from other airports, and other typical suburban sounds such as local vehicle traffic and yard work equipment.

DATA COLLECTION

Once the temporary noise monitoring period was complete, the noise event data was collected from MAA's Noise and Operating Monitoring System (NOMS) to analyze the times of noise events at the site to its database of aircraft radar flight paths. The NOMS conservatively attributes any noise event to an aircraft if the aircraft is within 8,000 feet of the measurement site at an altitude no greater than 10,000 feet. Noise events that occurred while aircraft were passing within the vicinity were associated with an actual aircraft flight and therefore assigned as aircraft noise events. Noise events that did not correlate with an aircraft overflight were assigned as community noise events. Using this methodology, some noise events that are correlated with aircraft overflights may include other community noise, which may or may not exceed the noise level from the aircraft overflight. **Figure 4** on the next page displays all arrivals and departures to and from BWI Marshall during the measurement period. **Figure 5** displays all arrivals and departures to and from BWI Marshall that were correlated with aircraft noise events.



Arrivals and Departures




Figure 4. All BWI Marshall Arrivals and Departures During the Measurement Period
Note: Green = Departures, Red = Arrivals




Figure 5. BWI Marshall Arrivals and Departures Correlated to Aircraft Noise Events During the Measurement Period
Note: Green = Departures, Red = Arrivals

Measured Noise Levels

NOISE METRICS

There are several key metrics that are used to describe aircraft and community noise on a single-event and cumulative basis. The appendix titled “How Do We Describe Aircraft Noise” provides a more detailed overview of the metrics which are discussed in this section. Single-event metrics such as Maximum A-Weighted Sound Level (Lmax) are indicators of the intrusiveness, loudness, or noisiness of individual noise events while cumulative metrics like Day-Night Average Sound Level (DNL) are generally used to measure long-term noise and are indicators of community annoyance and land use compatibility.

Figure 6 presents the range of maximum single-event sound levels for 360 aircraft overflights at the measurement site for the complete measurement period. For a particular noise event, such as an aircraft overflight, the loudest level at any instant during the event is the Lmax. For typical conversational speech at approximately 3 feet, speech is interrupted by noise levels at or above 65 dB. Any noise events shown in this figure with a maximum level at or above 65 dB would interrupt typical conversations outdoors (briefly for quieter events and longer for louder events). **Figure 7** shows common environmental A-weighted noise levels for typical outdoor sounds.




Figure 6. Maximum Single Event Aircraft Noise Levels




Figure 7. Common Environmental Noise Levels

Loudest Aircraft Events

Table 1 shows the top 15 loudest aircraft events that occurred during the measurement period including details about the date and time the event occurred, aircraft type, operation type, runway, and slant range (the line-of-sight distance between the receptor and the aircraft). Note that these events only represent the noisiest aircraft events at the measurement site, and the majority of aircraft overflights at the measurement site were less noisy than those shown in **Table 1**. It should also be noted that the top three flights are arrivals and departures Blue Angles flight demonstration squadron at Martin State Airport.

Note: In some cases, community events may occur simultaneously with aircraft overflights, causing aircraft overflights to have higher recorded sound levels.

Table 1. Top Fifteen Loudest Aircraft Events During the Measurement Period

Rank	Flight Time	Airline	Aircraft Type	Operation Type	Runway	Altitude (ft. AGL)	Slant Range (ft.)	Maximum Sound Level (dBA)
1	6/27/2026 14:31		Blue Angels - F/A-18F Super Hornet	Arrival	15 - MTN	1,056	5,236	88
2	6/25/2026 15:13		Blue Angels - F/A-18F Super Hornet	Arrival	15 - MTN	1,180	3,426	85
3	6/25/2026 12:07		Blue Angels - F/A-18F Super Hornet	Departure	15 - MTN	787	1,683	83
4	6/25/2026 20:53		Boeing 767-300	Departure	10	2,014	2,037	82
5	6/14/2026 16:03	N/A	Boeing 777-200	Departure	10	2,493	3,182	80
6	6/22/2026 12:14		Boeing 737-900	Departure	10	1,745	2,073	80
7	6/22/2026 10:55		Boeing 737-900	Departure	10	1,856	2,041	79
8	6/28/2026 1:50		Boeing 767-300	Departure	10	2,276	2,448	79
9	6/17/2026 20:56		Boeing 767-300	Departure	10	1,924	1,952	79
10	6/22/2026 11:11		Boeing 737-800	Departure	10	1,909	2,205	78
11	6/22/2026 11:36		Boeing 737-800	Departure	10	1,769	1,821	78
12	6/22/2026 11:55		Boeing 737-800	Departure	10	1,995	2,306	78
13	6/22/2026 14:41		Boeing 737-700	Arrival	28	928	1,463	78
14	6/18/2026 12:24		Airbus A300	Arrival	28	1,029	1,467	78
15	6/18/2026 19:17		Airbus A300	Arrival	28	987	1,368	77

Conclusion

DAY-NIGHT AVERAGE SOUND LEVEL

Figure 8 on the following page presents the cumulative DNL at the measurement site for the 16 complete days of the measurement period for community, aircraft, and total noise exposure. **Figure 9** on the following page presents the daily DNL at the site for aircraft noise exposure. DNL sums the noise from every noise event over the day. The formula for DNL gives an extra 10 decibel weighting to nighttime noise events to account for the intrusive nature of these events. The aircraft DNL ranged from 0 to 56 dB during the measurement period. The total aircraft DNL for the measurement period was 49 dB. The DNL for all recorded community noise events (wildlife, landscaping, weather, etc.) during the measurement period was 52 dB. The total DNL at the measurement site, which includes both aircraft and community noise events, was 54 dB.

AIRCRAFT OPERATIONS

Aircraft noise levels at this site are higher when BWI Marshall operates in east flow. During the measurement period, BWI Marshall operated in east flow 28% of the time and in west flow 72% of the time, which is a higher usage of west flow than the annual average of 70% west flow operations and 30% east flow operations.

MONITORING RESULTS

The results of the portable noise monitoring are for informational purposes only and capture the aircraft noise environment for a snapshot in time. The conditions during a monitoring period can vary greatly due to wind and weather (atmospheric conditions), the runway(s) in use at the time for arrivals and departures, and the number and type of operations occurring during the monitoring period. From the data collected, aircraft noise levels in terms of the DNL were calculated and resulted in a 16-day average of 49 dB.

GUIDELINES AND REGULATIONS

In Appendix A of 14 CFR Part 150, the Federal Aviation Administration provides guidelines for the compatibility of land uses with various annual DNL values. Code of Maryland Regulations (COMAR) 11.03.03.03 establishes limits for cumulative noise exposure for certain land uses around BWI Marshall. These guidelines consider residential land use to be noncompatible when the DNL is 75 dB or greater. For noise levels between 65 dB and 75 dB DNL, residential land use is considered noncompatible, but where the community determines that this land use must be allowed, measures to achieve greater than typical outdoor to indoor noise level reduction should be incorporated into building codes. The guidelines designate all land uses, including residential, as compatible for DNL values below 65 dB.






Figure 8. Cumulative Noise Exposure from Aircraft and Community Sources




Figure 9. Measured Daily Aircraft Noise Levels

More Information

ADDITIONAL RESOURCES

Website: www.bwiairport.com

X: @BWI_Airport

MAA'S NOISE PROGRAM

Information about Maryland Department of Transportation Maryland Aviation Administration's (MAA's) Noise Program activities can be found at marylandaviation.com. Frequent topics of interest include:

NOISE COMPLAINTS

MAA provides multiple methods to submit aircraft noise complaints, including an on-line form or 24-hour noise complaint and information hotline at 410-859-7021. MAA reviews noise complaints daily, and logs, reviews, and analyzes all noise complaints on a regular basis.

<https://marylandaviation.com/environmental/airport-noise/noise-complaints/>

QUARTERLY NOISE REPORTS

Each quarter, MAA prepares and publishes a quarterly noise report. The report provides information on operational trends (including the number of jet and cargo operations, and the number of nighttime operations), runway use, flight corridors/flight density maps, noise complaints received, outreach efforts, permanent noise monitoring data and MAA's noise assistance programs.

ENEWS EXPRESS

Stay up-to-date on planned runway closures, as well as other important aviation topics, by subscribing to the BWI Marshall eNews Express at <https://marylandaviation.com/environmental/airport-noise/enews-express-signup/>.

AIRPORT NOISE ZONE

The BWI Noise Abatement Plan and Airport Noise Zone, first established in 1976, includes a wide variety of strategies that are intended to reduce noise impacts for communities around the Airport while maintaining efficient airport operations. Noise abatement at BWI includes operational procedures such as aircraft arrival and departure procedures and a preferential runway use system intended to direct aircraft operations over less populated areas, where and when possible. Other elements of the Noise Abatement Plan include land use restrictions and programs such as land acquisition and soundproofing.

